

## SL-Series Modular Jack, RJ45, Cat6 Unshielded, Black



## Product Classification

|                              |   |
|------------------------------|---|
| <b>Regional Availability</b> | Asia   Australia/New Zealand   EMEA   Latin America |
| <b>Portfolio</b>             | NETCONNECT®   |
| <b>Product Type</b>          | Modular jack  |
| <b>Product Series</b>        | SL Series   |

## General Specifications

|  |   |
|--|---|
| <b>ANSI/TIA Category</b>               | 6   |
| <b>Cable Type</b>                      | Unshielded                                |
| <b>Color</b>                           | Black                                     |
| <b>Conductor Type</b>                  | Solid   Stranded                          |
| <b>Integrated Dust Cover Type</b>      | None                                      |
| <b>Mounting</b>                        | SL Series faceplates and panels           |
| <b>Termination Punchdowns, minimum</b> | 20 times                                  |
| <b>Termination Tool</b>                | 110 Punchdown tool   JTT Termination tool |
| <b>Termination Type</b>                | IDC                                       |
| <b>Transmission Standards</b>          | ANSI/TIA-568.2-D   ISO/IEC 11801 Class E  |
| <b>Wiring</b>                          | T568A   T568B                             |

## Dimensions

|               |                     |
|---------------|---------------------|
| <b>Height</b> | 16.13 mm   0.635 in |
| <b>Width</b>  | 14.48 mm   0.57 in  |
| <b>Depth</b>  | 30.48 mm   1.2 in   |

**Compatible Cable Diameter, maximum** 5.8 mm | 0.228 in

**Compatible Insulated Conductor Diameter, maximum** 1.45 mm | 0.057 in

**Contact Plating Thickness** 1.27  $\mu$ m

**Compatible Conductor Gauge, solid** 22–24 AWG

**Compatible Conductor Gauge, stranded** 22–26 AWG

## Electrical Specifications

**Contact Resistance, maximum** 20 mOhm

**Current Rating at Temperature** 1.5 A @ 20 °C | 1.5 A @ 68 °F

**Dielectric Withstand Voltage, RMS, contact-to-contact** 1,000 Vac @ 60 Hz

**Insulation Resistance, minimum** 500 MOhm

**Remote Powering** Fully supports the safe delivery of power over LAN cabling described by IEEE 802.3bt (Type 4) and complies with the unmating under electrical load requirements prescribed by IEC 60512-99-002

**PoE Durability** Supports IEEE 802.3bt Type 4 (90 W) applications greater than 3000 plug to jack mating cycles

**Safety Voltage Rating** 150 Vac

## Material Specifications

**Contact Base Material** Beryllium copper

**Contact Plating Material** Gold

**IDC Termination Material** Phosphor Bronze

**Material Type** PC+ABS

**Termination Contact Plating** Tin

## Mechanical Specifications

**Plug Retention Force, minimum** 50 N | 11.24 lbf

**Plug to Jack Mating Cycles** Complies to IEC 60603-7 series

## Environmental Specifications

|                              |                                      |
|------------------------------|--------------------------------------|
| <b>Operating Temperature</b> | -10 °C to +60 °C (+14 °F to +140 °F) |
| <b>Storage Temperature</b>   | -40 °C to +70 °C (-40 °F to +158 °F) |
| <b>Relative Humidity</b>     | Up to 95%, non-condensing            |
| <b>Flammability Rating</b>   | UL 94 V-0                            |
| <b>Safety Standard</b>       | cULus                                |

## Packaging and Weights

|                           |     |
|---------------------------|-----|
| <b>Packaging quantity</b> | 1   |
| <b>Packaging Type</b>     | Bag |

## Regulatory Compliance/Certifications

| <b>Agency</b> | <b>Classification</b>  |
|---------------|--|
| CHINA-ROHS    | Below maximum concentration value  |
| RCM           | Compliant to electrical safety & telecommunications requirements   |
| REACH-SVHC    | Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a> |
| ROHS          | Compliant  |
| UK-ROHS       | Compliant  |

